



Bowers & Wilkins

603 S3

Technical Information



Technical features

Decoupled Double Dome Titanium tweeter
Continuum™ cone FST™ midrange
Paper bass cones
Flowport™

Description

3-way vented-box system

Drive units

1x ø25mm (1 in) Titanium Dome high-frequency
1x ø150mm (6 in) Continuum cone FST midrange
2x ø165mm (6.5 in) Paper bass cone

Frequency range

-6dB 29Hz - 33kHz

Frequency response

(+/-3dB from reference axis)

46Hz - 28kHz ±3dB

Sensitivity

(on axis at 2.83Vrms at 1m)

90dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 100Hz - 22kHz
<0.5% 350Hz - 12kHz

Nominal impedance

8Ω (minimum 3.0Ω)

Recommended amplifier power

30W - 200W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 985 mm (38.8 in) cabinet only
1,020 mm (40.2 in) including plinth

Width: 190 mm (7.5 in) cabinet only
260 mm (10.2 in) including plinth

Depth: 340 mm (13.4 in) cabinet only
368 mm (14.5 in) including grille and terminals
402 mm (15.8 in) including plinth

Net weight

27.5kg (60.6lbs)

Finishes

Cabinet: Black
White
Oak

Grille: Black (Black)
Grey (White and Oak)