



Bowers & Wilkins

805 D4 Signature

Technical Information

**Technical features**

Diamond tweeter
 Solid Body Tweeter-on-Top
 Continuum™ cone bass/midrange
 Matrix™
 Anti-Resonance plug
 Flowport™

Description

2-way vented-box system

Drive units

1x ø25mm (1in) Diamond Dome high-frequency
 1x ø165mm (6.5in) Continuum™ cone bass/midrange

Frequency range

-6dB 34Hz to 35kHz

Frequency response

(+/-3dB from reference axis)

42Hz to 28kHz ±3dB

Sensitivity

(on axis at 2.83Vrms at 1m)

88dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)

<1 % 90Hz - 20kHz

<0.3% 120Hz - 20kHz

Nominal impedance

8Ω (minimum 4.6Ω)

Recommended amplifier power

50W - 120W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 440mm (17.3in)

Width: 240mm (9.4in)

Depth: 373mm (14.7in)

Net weight

15.6kg (34.3lbs)

Finishes

Cabinet: California Burl Gloss
 Midnight Blue Metallic

Grille: Black

